

Thermal Performance Data

Visions 3500 Single Hung Picture (9310)

(non J-channel)




ENERGY PERFORMANCE DATA								ENERGY STAR		CANADIAN ENERGY PERFORMANCE DATA				ENERGY STAR					
NFRC Total Unit Calculations ^a								US ENERGY STAR V 6.0		U-Value (metric)	Maximum Air Leakage L/s/m ²	Air Infiltration/Exfiltration Average	Energy Rating	CANADA ENERGY STAR v 4.1					
Grille Option	Glazing thickness	Glazing Option ^b	CPD #	U Value	Solar Heat Gain Coefficient	Visible Light Transmittance	Condensation Resistance Rating	N	NC					SC	S	1	2	3	
No GIA or SDL	3/4"	Clear Insul	WEA-N-274-00575-00001	0.45	0.67	0.70	45					2.56	0.6	0.05	23				
	3/4"	Insul Low-E	WEA-N-274-00594-00001	0.30	0.36	0.61	57		Y			1.70	0.6	0.05	24				
	3/4"	Insul Low E w/Argon	WEA-N-274-00620-00001	0.26	0.36	0.61	61	Y	Y			1.48	0.6	0.05	28	Y			
	3/4"	Bronze Low E	WEA-N-274-00594-00011	0.30	0.34	0.45	57		Y			1.70	0.6	0.05	22				
	3/4"	Bronze Low E w/Argon	WEA-N-274-00620-00011	0.26	0.34	0.45	61	Y	Y			1.48	0.6	0.05	27	Y			
	3/4"	Insul Low-E 340	WEA-N-274-00798-00001	0.30	0.16	0.33	57		Y	Y	Y		1.70	0.6	0.05	12			
	3/4"	Insul Low-E 340 w/Argon	WEA-N-274-00849-00001	0.26	0.15	0.33	61	Y	Y	Y	Y		1.48	0.6	0.05	16	Y		
	3/4"	Zo-e-shield 5	WEA-N-274-00652-00001	0.30	0.24	0.55	57		Y	Y	Y	Y	1.70	0.6	0.05	17			
	3/4"	Zo-e-shield 5 w/ Argon	WEA-N-274-00712-00001	0.26	0.24	0.55	61	Y	Y	Y	Y		1.48	0.6	0.05	21	Y		
	3/4"	Zo-e-shield 5 Extreme	WEA-N-274-00670-00001	0.24	0.23	0.54	45	Y	Y	Y	Y		1.36	0.6	0.05	23	Y	Y	
	3/4"	Zo-e-shield 5 Extreme w/ Argon	WEA-N-274-00730-00001	0.21	0.23	0.54	48	Y	Y	Y	Y		1.19	0.6	0.05	27	Y	Y	Y
	3/4"	Zo-e-shield 6	WEA-N-274-00679-00001	0.32	0.24	0.54	54				Y		1.82	0.6	0.05	14			
	3/4"	Zo-e-shield 6 w/ Argon	WEA-N-274-00739-00001	0.27	0.24	0.54	59	Y	Y	Y	Y		1.53	0.6	0.05	20	Y		
	1"	Zo-e-shield 7 (Triple Glazed)	WEA-N-274-01096-00001	0.23	0.22	0.44	67	Y	Y	Y	Y		1.31	0.6	0.05	24	Y	Y	
	1"	Zo-e-shield 7 w/ Argon (Triple Glazed)	WEA-N-274-01098-00001	0.19	0.22	0.44	71	Y	Y	Y	Y		1.08	0.6	0.05	29	Y	Y	Y
	Less Than 1" GIA or SDL	3/4"	Clear Insul	WEA-N-274-00575-00004	0.45	0.60	0.63	45					2.56	0.6	0.05	19			
3/4"		Insul Low-E	WEA-N-274-00594-00004	0.30	0.32	0.55	57		Y			1.70	0.6	0.05	21				
3/4"		Insul Low E w/Argon	WEA-N-274-00620-00004	0.26	0.32	0.55	61	Y	Y			1.48	0.6	0.05	26	Y			
3/4"		Bronze Low E	WEA-N-274-00594-00014	0.30	0.31	0.41	57		Y			1.70	0.6	0.05	21				
3/4"		Bronze Low E w/Argon	WEA-N-274-00620-00014	0.26	0.31	0.41	61	Y	Y			1.48	0.6	0.05	25	Y			
3/4"		Insul Low-E 340	WEA-N-274-00798-00004	0.30	0.15	0.30	57		Y	Y	Y		1.70	0.6	0.05	11			
3/4"		Insul Low-E 340 w/Argon	WEA-N-274-00849-00004	0.26	0.14	0.30	61	Y	Y	Y	Y		1.48	0.6	0.05	16			
3/4"		Zo-e-shield 5	WEA-N-274-00652-00004	0.30	0.22	0.50	57		Y	Y	Y	Y	1.70	0.6	0.05	15			
3/4"		Zo-e-shield 5 w/ Argon	WEA-N-274-00712-00004	0.26	0.21	0.50	61	Y	Y	Y	Y		1.48	0.6	0.05	20	Y		
3/4"		Zo-e-shield 5 Extreme	WEA-N-274-00670-00004	0.24	0.21	0.48	45	Y	Y	Y	Y		1.36	0.6	0.05	22	Y	Y	
3/4"		Zo-e-shield 5 Extreme w/ Argon	WEA-N-274-00730-00004	0.21	0.21	0.48	48	Y	Y	Y	Y		1.19	0.6	0.05	26	Y	Y	Y
3/4"		Zo-e-shield 6	WEA-N-274-00680-00003	0.34	0.22	0.49	54				Y		1.93	0.6	0.05	10			
3/4"		Zo-e-shield 6 w/ Argon	WEA-N-274-00740-00003	0.29	0.22	0.49	59		Y	Y	Y	Y	1.65	0.6	0.05	17			
1"		Zo-e-shield 7 (Triple Glazed)	WEA-N-274-01097-00003	0.25	0.20	0.40	67	Y	Y	Y	Y		1.42	0.6	0.05	20	Y		
1"	Zo-e-shield 7 w/ Argon (Triple Glazed)	WEA-N-274-01099-00003	0.21	0.20	0.40	71	Y	Y	Y	Y		1.19	0.6	0.05	25	Y	Y	Y	
1" or Over GIA or SDL	3/4"	Clear Insul	WEA-N-274-00575-00005	0.45	0.54	0.56	45					2.56	0.6	0.05	15				
	3/4"	Insul Low-E	WEA-N-274-00594-00005	0.30	0.29	0.49	57		Y			1.70	0.6	0.05	19				
	3/4"	Insul Low E w/Argon	WEA-N-274-00620-00005	0.26	0.29	0.49	61	Y	Y			1.48	0.6	0.05	24	Y			
	3/4"	Bronze Low E	WEA-N-274-00594-00015	0.30	0.28	0.36	57		Y			1.70	0.6	0.05	19				
	3/4"	Bronze Low E w/Argon	WEA-N-274-00620-00015	0.26	0.28	0.36	61	Y	Y			1.48	0.6	0.05	24	Y			
	3/4"	Insul Low-E 340	WEA-N-274-00798-00005	0.30	0.13	0.26	57		Y	Y	Y		1.70	0.6	0.05	10			
	3/4"	Insul Low-E 340 w/Argon	WEA-N-274-00849-00005	0.26	0.13	0.26	61	Y	Y	Y	Y		1.48	0.6	0.05	15			
	3/4"	Zo-e-shield 5	WEA-N-274-00652-00005	0.30	0.20	0.44	57		Y	Y	Y	Y	1.70	0.6	0.05	14			
	3/4"	Zo-e-shield 5 w/ Argon	WEA-N-274-00712-00005	0.26	0.19	0.44	61	Y	Y	Y	Y		1.48	0.6	0.05	19	Y		
	3/4"	Zo-e-shield 5 Extreme	WEA-N-274-00670-00005	0.24	0.19	0.43	45	Y	Y	Y	Y		1.36	0.6	0.05	21	Y	Y	
	3/4"	Zo-e-shield 5 Extreme w/ Argon	WEA-N-274-00730-00005	0.21	0.19	0.43	48	Y	Y	Y	Y		1.19	0.6	0.05	25	Y	Y	Y
	3/4"	Zo-e-shield 6	WEA-N-274-00680-00004	0.34	0.20	0.43	54				Y		1.93	0.6	0.05	9			
	3/4"	Zo-e-shield 6 w/ Argon	WEA-N-274-00740-00004	0.29	0.20	0.43	59		Y	Y	Y	Y	1.65	0.6	0.05	15			
	1"	Zo-e-shield 7 (Triple Glazed)	WEA-N-274-01097-00004	0.25	0.18	0.35	67	Y	Y	Y	Y		1.42	0.6	0.05	19	Y		
	1"	Zo-e-shield 7 w/ Argon (Triple Glazed)	WEA-N-274-01099-00004	0.21	0.18	0.35	71	Y	Y	Y	Y		1.19	0.6	0.05	24	Y	Y	Y

^a Total Unit calculations are derived from computer simulations that are then verified by 3rd party testing in accordance with NFRC 100-2004, NFRC 200-2004, and NFRC 500-2004.

Revised 8/14/17

^b Published values reflect 3mm/3mm glass lite thicknesses.

US Qualification Criteria	Climate Zone	U-Factor	*SHGC	
 As of January 2016	Northern	<=0.27	Any	Prescriptive
		=0.28	>=0.32	Equivalent Energy Performance
		=0.29	>=0.37	
		=0.30	>=0.42	
	North-Central	<=0.30	<=0.40	
	South-Central	<=0.30	<=0.25	
Southern	<=0.40	<=0.25		

* SHGC = Solar Heat Gain Coefficient
Air Leakage <= 0.3 cfm/ft²