

Thermal Performance Data

Visions 3500 Double Hung Picture (9311)

(J-channel)




ENERGY PERFORMANCE DATA								ENERGY STAR		CANADIAN ENERGY PERFORMANCE DATA				ENERGY STAR					
NFRC Total Unit Calculations ^a								US ENERGY STAR V 6.0		U-Value (metric)	Maximum Air Leakage L/s/m ²	Air Infiltration/Exfiltration Average	Energy Rating	CANADA ENERGY STAR v 4.1					
Grille Option	Glazing thickness	Glazing Option ^b	CPD #	U Value	Solar Heat Gain Coefficient	Visible Light Transmittance	Condensation Resistance Rating	N	NC					SC	S	1	2	3	
No GIA or SDL	3/4"	Clear Insul	WEA-N-306-00001-00001	0.45	0.68	0.71	45					2.56	-	0.00	0				
	3/4"	Insul Low-E	WEA-N-306-00016-00001	0.30	0.36	0.62	57		Y			1.70	-	0.00	0				
	3/4"	Insul Low E w/Argon	WEA-N-306-00046-00001	0.26	0.36	0.62	61	Y	Y			1.48	-	0.00	0				
	3/4"	Bronze Low E	WEA-N-306-00021-00001	0.30	0.34	0.45	58		Y			1.70	0.6	0.05	22				
	3/4"	Bronze Low E w/Argon	WEA-N-306-00051-00001	0.26	0.34	0.45	61	Y	Y			1.48	0.6	0.05	27	Y			
	3/4"	Insul Low-E 340	WEA-N-306-00180-00001	0.30	0.16	0.33	58		Y	Y	Y		1.70	-	0.00	0			
	3/4"	Insul Low-E 340 w/Argon	WEA-N-306-00202-00001	0.26	0.15	0.33	61	Y	Y	Y	Y		1.48	-	0.00	0			
	3/4"	Zo-e-shield 5	WEA-N-306-00066-00001	0.29	0.24	0.56	58		Y	Y	Y	Y	1.65	-	0.00	0			
	3/4"	Zo-e-shield 5 w/ Argon	WEA-N-306-00120-00001	0.25	0.24	0.56	62	Y	Y	Y	Y		1.42	-	0.00	0			
	3/4"	Zo-e-shield 5 Extreme	WEA-N-306-00086-00001	0.24	0.23	0.54	45	Y	Y	Y	Y		1.36	-	0.00	0			
	3/4"	Zo-e-shield 5 Extreme w/ Argon	WEA-N-306-00140-00001	0.21	0.23	0.54	49	Y	Y	Y	Y		1.19	-	0.00	0			
	3/4"	Zo-e-shield 6	WEA-N-306-00091-00001	0.32	0.24	0.54	54				Y		1.82	0.6	0.05	14			
	3/4"	Zo-e-shield 6 w/ Argon	WEA-N-306-00145-00001	0.26	0.24	0.54	59	Y	Y	Y	Y		1.48	0.6	0.05	21	Y		
	1"	Zo-e-shield 7 (Triple Glazed)	WEA-N-306-00213-00001	0.23	0.22	0.44	67	Y	Y	Y	Y		1.31	0.6	0.05	24	Y	Y	
	1"	Zo-e-shield 7 w/ Argon (Triple Glazed)	WEA-N-306-00215-00001	0.19	0.22	0.44	72	Y	Y	Y	Y		1.08	0.6	0.05	29	Y	Y	Y
Less Than 1" GIA or SDL	3/4"	Clear Insul	WEA-N-306-00001-00002	0.45	0.61	0.63	45					2.56	-	0.00	0				
	3/4"	Insul Low-E	WEA-N-306-00016-00002	0.30	0.33	0.55	57		Y			1.70	-	0.00	0				
	3/4"	Insul Low E w/Argon	WEA-N-306-00046-00002	0.26	0.32	0.55	61	Y	Y			1.48	-	0.00	0				
	3/4"	Bronze Low E	WEA-N-306-00021-00004	0.30	0.31	0.41	58		Y			1.70	0.6	0.05	21				
	3/4"	Bronze Low E w/Argon	WEA-N-306-00051-00004	0.26	0.31	0.41	61	Y	Y			1.48	0.6	0.05	25	Y			
	3/4"	Insul Low-E 340	WEA-N-306-00180-00002	0.30	0.15	0.30	58		Y	Y	Y		1.70	-	0.00	0			
	3/4"	Insul Low-E 340 w/Argon	WEA-N-306-00202-00002	0.26	0.14	0.30	61	Y	Y	Y	Y		1.48	-	0.00	0			
	3/4"	Zo-e-shield 5	WEA-N-306-00066-00002	0.29	0.22	0.50	58		Y	Y	Y	Y	1.65	-	0.00	0			
	3/4"	Zo-e-shield 5 w/ Argon	WEA-N-306-00120-00002	0.25	0.21	0.50	62	Y	Y	Y	Y		1.42	-	0.00	0			
	3/4"	Zo-e-shield 5 Extreme	WEA-N-306-00086-00002	0.24	0.21	0.49	45	Y	Y	Y	Y		1.36	-	0.00	0			
	3/4"	Zo-e-shield 5 Extreme w/ Argon	WEA-N-306-00140-00002	0.21	0.21	0.49	49	Y	Y	Y	Y		1.19	-	0.00	0			
	3/4"	Zo-e-shield 6	WEA-N-306-00092-00003	0.33	0.22	0.49	54				Y		1.87	0.6	0.05	12			
	3/4"	Zo-e-shield 6 w/ Argon	WEA-N-306-00146-00003	0.28	0.22	0.49	59		Y	Y	Y	Y	1.59	0.6	0.05	18	Y		
	1"	Zo-e-shield 7 (Triple Glazed)	WEA-N-306-00214-00003	0.24	0.20	0.40	67	Y	Y	Y	Y		1.36	0.6	0.05	22	Y	Y	
	1"	Zo-e-shield 7 w/ Argon (Triple Glazed)	WEA-N-306-00216-00003	0.20	0.20	0.40	72	Y	Y	Y	Y		1.14	0.6	0.05	27	Y	Y	Y
1" or Over GIA or SDL	3/4"	Clear Insul	WEA-N-306-00001-00005	0.45	0.55	0.56	45					2.56	-	0.00	0				
	3/4"	Insul Low-E	WEA-N-306-00016-00005	0.30	0.29	0.49	57		Y			1.70	-	0.00	0				
	3/4"	Insul Low E w/Argon	WEA-N-306-00046-00005	0.26	0.29	0.49	61	Y	Y			1.48	-	0.00	0				
	3/4"	Bronze Low E	WEA-N-306-00021-00005	0.30	0.28	0.36	58		Y			1.70	0.6	0.05	19				
	3/4"	Bronze Low E w/Argon	WEA-N-306-00051-00005	0.26	0.28	0.36	61	Y	Y			1.48	0.6	0.05	24	Y			
	3/4"	Insul Low-E 340	WEA-N-306-00180-00005	0.30	0.13	0.27	58		Y	Y	Y		1.70	-	0.00	0			
	3/4"	Insul Low-E 340 w/Argon	WEA-N-306-00202-00005	0.26	0.13	0.27	61	Y	Y	Y	Y		1.48	-	0.00	0			
	3/4"	Zo-e-shield 5	WEA-N-306-00066-00005	0.29	0.20	0.44	58		Y	Y	Y	Y	1.65	-	0.00	0			
	3/4"	Zo-e-shield 5 w/ Argon	WEA-N-306-00120-00005	0.25	0.19	0.44	62	Y	Y	Y	Y		1.42	-	0.00	0			
	3/4"	Zo-e-shield 5 Extreme	WEA-N-306-00086-00005	0.24	0.19	0.43	45	Y	Y	Y	Y		1.36	-	0.00	0			
	3/4"	Zo-e-shield 5 Extreme w/ Argon	WEA-N-306-00140-00005	0.21	0.19	0.43	49	Y	Y	Y	Y		1.19	-	0.00	0			
	3/4"	Zo-e-shield 6	WEA-N-306-00092-00004	0.33	0.20	0.43	54				Y		1.87	0.6	0.05	11			
	3/4"	Zo-e-shield 6 w/ Argon	WEA-N-306-00146-00004	0.28	0.20	0.43	59		Y	Y	Y	Y	1.59	0.6	0.05	17	Y		
	1"	Zo-e-shield 7 (Triple Glazed)	WEA-N-306-00214-00004	0.24	0.18	0.35	67	Y	Y	Y	Y		1.36	0.6	0.05	21	Y	Y	
	1"	Zo-e-shield 7 w/ Argon (Triple Glazed)	WEA-N-306-00216-00004	0.20	0.18	0.35	72	Y	Y	Y	Y		1.14	0.6	0.05	25	Y	Y	Y

^a Total Unit calculations are derived from computer simulations that are then verified by 3rd party testing in accordance with NFRC 100-2004, NFRC 200-2004, and NFRC 500-2004.

Revised 8/14/17

^b Published values reflect 3mm/3mm glass lite thicknesses.

US Qualification Criteria	Climate Zone	U-Factor	*SHGC	
 As of January 2016	Northern	<=0.27	Any	Prescriptive
		=0.28	>=0.32	Equivalent Energy Performance
		=0.29	>=0.37	
		=0.30	>=0.42	
	North-Central	<=0.30	<=0.40	
	South-Central	<=0.30	<=0.25	
Southern	<=0.40	<=0.25		

* SHGC = Solar Heat Gain Coefficient
Air Leakage <= 0.3 cfm/ft²