

# Opening Specifications

Visions 3500 Single Slider Windows (9407/9408)

Rev 6/17



Call Size	Sq. Ft. Clear Opening	Clear Opening		Sq. Ft. Daylight Opening	Sq. Ft. Vent	Floor to Bottom of Clear Opening <sup>a</sup>	Sq. Ft. Overall Unit Area <sup>b</sup>
		Width <sup>c</sup>	Height				
2620	1.47	10.86	19.50	2.94	1.47	60.25	4.81
2626	1.92	10.86	25.50	3.89	1.92	54.25	6.04
2630	2.38	10.86	31.50	4.83	2.38	48.25	7.27
2636	2.83	10.86	37.50	5.78	2.83	42.25	8.50
2640	3.28	10.86	43.50	6.72	3.28	36.25	9.73
2646	3.73	10.86	49.50	7.67	3.73	30.25	10.96
2650	4.19	10.86	55.50	8.61	4.19	24.25	12.19
3020	1.88	13.86	19.50	3.72	1.88	60.25	5.79
3026	2.45	13.86	25.50	4.92	2.45	54.25	7.27
3030	3.03	13.86	31.50	6.11	3.03	48.25	8.75
3036	3.61	13.86	37.50	7.31	3.61	42.25	10.23
3040	4.19	13.86	43.50	8.50	4.19	36.25	11.71
3046	4.77	13.86	49.50	9.70	4.77	30.25	13.19
3050	5.34	13.86	55.50	10.89	5.34	24.25	14.67
3620	2.28	16.86	19.50	4.50	2.28	60.25	6.77
3626	2.99	16.86	25.50	5.95	2.99	54.25	8.50
3630	3.69	16.86	31.50	7.39	3.69	48.25	10.23
3636	4.39	16.86	37.50	8.84	4.39	42.25	11.96
3640	5.09	16.86	43.50	10.28	5.09	36.25	13.69
3646	5.80	16.86	49.50	11.73	5.80	30.25	15.42
3650	6.50	16.86	55.50	13.17	6.50	24.25	17.15
4020	2.69	19.86	19.50	5.28	2.69	60.25	7.75
4026	3.52	19.86	25.50	6.97	3.52	54.25	9.73
4030	4.35	19.86	31.50	8.67	4.35	48.25	11.71
4036	5.17	19.86	37.50	10.36	5.17	42.25	13.69
4040	6.00	19.86	43.50	12.06	6.00	36.25	15.67
4046	6.83	19.86	49.50	13.75	6.83	30.25	17.65
4050	7.66	19.86	55.50	15.45	7.66	24.25	19.63
4620	3.10	22.86	19.50	6.06	3.10	60.25	8.73
4626	4.05	22.86	25.50	8.00	4.05	54.25	10.96
4630	5.00	22.86	31.50	9.95	5.00	48.25	13.19
4636	5.95	22.86	37.50	11.89	5.95	42.25	15.42
4640	6.91	22.86	43.50	13.84	6.91	36.25	17.65
4646	7.86	22.86	49.50	15.78	7.86	30.25	19.88
4650	8.81	22.86	55.50	17.73	8.81	24.25	22.11
5020	3.50	25.86	19.50	6.84	3.50	60.25	9.71
5026	4.58	25.86	25.50	9.03	4.58	54.25	12.19
5030	5.66	25.86	31.50	11.23	5.66	48.25	14.67
5036	6.74	25.86	37.50	13.42	6.74	42.25	17.15
5040	7.81	25.86	43.50	15.62	7.81	36.25	19.63
5046	8.89	25.86	49.50	17.81	8.89	30.25	22.11
5050	9.97	25.86	55.50	20.01	9.97	24.25	24.59
6020	4.31	31.86	19.50	8.39	4.31	60.25	11.67
6026	5.64	31.86	25.50	11.09	5.64	54.25	14.65
6030	6.97	31.86	31.50	13.78	6.97	48.25	17.63
6036	8.30	31.86	37.50	16.48	8.30	42.25	20.61
6040	9.63	31.86	43.50	19.17	9.63	36.25	23.59
6046	10.95	31.86	49.50	21.87	10.95	30.25	26.56
6050	12.28	31.86	55.50	24.56	12.28	24.25	29.54

Shaded sizes meet or exceed egress opening requirements per 2006 IBC (International Building Code) minimum dimensions of 20" clear opening width, 24" clear opening height, 5.7 sq. ft. clear opening and floor to bottom of clear opening not to exceed 44".

<sup>a</sup> Floor to bottom of clear opening dimensions are based on a 82" jamb height of a 6-10 door.

<sup>b</sup> Sq. Ft. Overall Unit Area is calculated on the jamb dimension.

<sup>c</sup> Clear opening width calculations were taken at 6° to the frame. Check local codes for egress compliance.

# Opening Specifications

## Visions 3500 Triple Slider Windows (9407/9408)

(1/4 - 1/2 - 1/4)



Call Size	Sq. Ft. Clear Opening	Clear Opening		Sq. Ft. Daylight Opening	Sq. Ft. Vent	Floor to Bottom of Clear Opening <sup>a</sup>	Sq. Ft. Overall Unit Area <sup>b</sup>
		Width <sup>c</sup>	Height				
6030	3.03	13.86	31.50	13.18	3.03	48.25	17.63
6036	3.61	13.86	37.50	15.76	3.61	42.25	20.61
6040	4.19	13.86	43.50	18.34	4.19	36.25	23.59
6046	4.77	13.86	49.50	20.92	4.77	30.25	26.56
6050	5.34	13.86	55.50	23.49	5.34	24.25	29.54
7030	3.69	16.86	31.50	15.74	3.69	48.25	20.59
7036	4.39	16.86	37.50	18.82	4.39	42.25	24.06
7040	5.09	16.86	43.50	21.90	5.09	36.25	27.54
7046	5.80	16.86	49.50	24.97	5.80	30.25	31.02
7050	6.50	16.86	55.50	28.05	6.50	24.25	34.50
8030	4.35	19.86	31.50	18.30	4.35	48.25	23.54
8036	5.17	19.86	37.50	21.88	5.17	42.25	27.52
8040	6.00	19.86	43.50	25.45	6.00	36.25	31.50
8046	6.83	19.86	49.50	29.03	6.83	30.25	35.48
8050	7.66	19.86	55.50	32.61	7.66	24.25	39.46

Shaded sizes meet or exceed egress opening requirements per 2006 IBC (International Building Code) minimum dimensions of 20" clear opening width, 24" clear opening height, 5.7 sq. ft. clear opening and floor to bottom of clear opening not to exceed 44".

<sup>a</sup> Floor to bottom of clear opening dimensions are based on a 82" jamb height of a 6-10 door.

<sup>b</sup> Sq. Ft. Overall Unit Area is calculated on the jamb dimension.

<sup>c</sup> Clear opening width calculations were taken at 6° to the frame. Check local codes for egress compliance.

<sup>d</sup> These windows meet or exceed emergency escape and rescue opening requirements if installed lower in the wall so the "Floor to Bottom of Clear Opening Height" does not exceed 44".

## Visions 3500 Triple Slider Windows (9407/9408)

(1/3 - 1/3 - 1/3)

Call Size	Sq. Ft. Clear Opening	Clear Opening		Sq. Ft. Daylight Opening	Sq. Ft. Vent	Floor to Bottom of Clear Opening <sup>a</sup>	Sq. Ft. Overall Unit Area <sup>b</sup>
		Width <sup>c</sup>	Height				
6030	4.409	20.16	31.50	13.18	4.41	48.25	17.63
6036	5.249	20.16	37.50	15.76	5.25	42.25	20.61
6040	6.088	20.155	43.5	18.34	6.09	36.25	23.59
6046	6.928	20.155	49.5	20.92	6.93	30.25	26.56
6050	7.768	20.155	55.5	23.49	7.77	24.25	29.54
7030	5.284	24.16	31.50	15.74	5.28	48.25	20.59
7036	6.290	24.155	37.5	18.82	6.29	42.25	24.06
7040	7.297	24.155	43.5	21.90	7.30	36.25	27.54
7046	8.303	24.155	49.5	24.97	8.30	30.25	31.02
7050	9.310	24.155	55.5	28.05	9.31	24.25	34.50
8030 <sup>d</sup>	6.159	28.16	31.50	18.30	6.16	48.25	23.54
8036	7.332	28.155	37.5	21.88	7.33	42.25	27.52
8040	8.505	28.155	43.5	25.45	8.51	36.25	31.50
8046	9.678	28.155	49.5	29.03	9.68	30.25	35.48
8050	10.851	28.155	55.5	32.61	10.85	24.25	39.46